

## CR-2 AF/CR-2 Plus AF

### Non-Mydriatic Retinal Cameras



*The CR-2 PLUS AF camera is shown with optional accessories.*

### Mobile Teleretinal Solution

Canon non-mydriatic, high-resolution retinal camera systems can be made transportable to conduct mobile, teleretinal, non-dilated eye screenings to support telehealth wellness programs at off-site, remote locations. The camera system, including laptop computer and image management software, can be transported using a customized rolling travel case equipped with top and side carry handles and wheels. Canon imageSPECTRUM image management software is a scalable platform that can provide fully automated, DICOM-compliant functionality to streamline network communication with EHR/EMR or PACS data storage systems.

#### Features:

- Canon retinal cameras include auto functionality with auto-focus/capture/exposure
- Canon EOS-dedicated, high-resolution digital camera (24 megapixel or higher)
- Small Pupil Retinal Camera Mode facilitates imaging pupil sizes down to 3.3 mm
- Canon imageSPECTRUM software includes Red-Free and Opacity Suppression digital filters
- Custom Hard-shell Travel Case is designed to transport Canon retinal non-myd camera and laptop

#### Canon Teleretinal Solution Suggested Components:

- Canon CR-2 AF/CR-2 Plus AF Non-Mydriatic Retinal Camera with dedicated EOS camera
- Laptop with Laptop Arm and Tray
- Hard-shell Travel Case
- Motorized Instrument Table
- Operator and Patient Stools

# Mobile Teleretinal Solution

## Digital Non-Mydriatic Retinal Camera

Specifications			
General			
Type	Digital Retinal Camera, Non-Mydriatic		
Type of Photography	<b>CR-2 AF:</b> Anterior, Stereo, Color, Digital Red-free, Digital Cobalt	<b>CR-2 PLUS AF:</b> Anterior, Stereo, Color, Digital Red-free, Digital Cobalt, Fundus AutoFluorescence (FAF)	
Angle of View	45° (35° SP Mode)		
Magnification	2x Digital		
Minimal Pupil Size	4.0 mm (3.3 mm SP mode)		
Focus Adjustment Type	Split-Line Adjustment		
Patient Diopter Compensation Range	<b>Without Compensation Lens:</b> -10 D to +15 D	<b>With "-" Compensation Lens:</b> -31 D to -7 D <b>With "+" Compensation Lens:</b> +11 D to +33 D	
Light Source	<b>Observation:</b> Infrared LED		
Type of Photography	<b>CR-2 AF:</b> White LED	<b>CR-2 PLUS AF:</b> Xenon Tube	
Canthus Mark	420 mm from base		
Internal Eye Fixation	LED Dot Matrix; Movable Fixation		
External Eye Fixation	White LED (Sold Separately)		
Working Distance	35 mm		
Working Distance Adjustment	<b>Fundus Observation:</b> Working Distance Dots		
Sensor Resolution	<b>CR-2 AF:</b> 24 megapixels or more	<b>CR-2 PLUS AF:</b> 24 megapixels or more	
Camera	<b>CR-2 AF:</b> Dedicated EOS Camera for CR-2 AF (Bundled)	<b>CR-2 PLUS AF:</b> Dedicated EOS Camera for CR-2 PLUS AF (Bundled)	
Monitor	3.0-inch Color LCD Monitor External Monitor (optional)		
Auto Function	Selectable Auto Focus, Auto Capture, Auto Exposure		
Mount Movement	<b>Front and Back:</b> 70 mm	<b>Side to Side:</b> 100 mm	<b>Up and Down:</b> 32 mm
Chin Rest Movement	62 mm		
Electrical and Environmental			
PC Interface	USB 1.1, USB 2.0		
Power Supply	AC 100-240 V, 50/60 Hz		
Operating Environment	<b>Temperature:</b> 50° to 86° Fahrenheit (10° to 35° Celsius)	<b>Humidity:</b> 30% to 90% RH (No Condensation) Atmospheric Pressure: 700 to 1060 hPa	
Physical Characteristics			
Dimensions (H x W x D)	<b>CR-2 AF:</b> 18.6" x 12" x 19.7" (473 mm x 305 mm x 500 mm)	<b>CR-2 PLUS AF:</b> 20.2" x 12" x 19.7" (513 mm x 305 mm x 500 mm)	
Weight	<b>CR-2 AF:</b> 33 lb. (15 kg)	<b>CR-2 PLUS AF:</b> 43.9 lb. (19.9 kg)	
Optional Accessories			
AutoMosaic Function, External Fixation Target, Motorized Table, Auxiliary Monitor			

**To schedule a demo or for additional information, call 1-833-521-3937 or visit our website.**

Follow us: <https://us.medical.canon>



@CanonMedicalUS



Canon Medical Systems USA, Inc.



+CanonMedicalUS

CANON MEDICAL SYSTEMS USA, INC.

<https://us.medical.canon> | 2441 Michelle Drive, Tustin CA 92780 | 800.421.1968

©Canon Medical Systems, USA 2020. All rights reserved. Design and specifications are subject to change without notice. Made for Life is a trademark of Canon Medical Systems Corporation. Google+ logo and YouTube logo are trademarks of Google Inc. TWITTER, TWEET, RETWEET and the Twitter logo are trademarks of Twitter, Inc. or its affiliates. LinkedIn, the LinkedIn logo, the IN logo and InMail are registered trademarks or trademarks of LinkedIn Corporation and its affiliates in the United States and/or other countries.

ECCSS13584US

*Made For life*